

APPENDIX

Check your report for the list of topics relevant to your inspection

<u>BUILDING FAULTS: CAUSES, PREVENTION, REPAIR</u>	5
<u>Cracking in buildings</u>	5
Overview	5
Footings and foundations	5
What can I do about it?	6
Drainage from hard surfaces	6
Drainage to and from sloping sites	6
Excavated sites and underground garages	7
Excessive soil moisture	7
Uneven rainfall is bad news	7
Tree roots	7
Leaking plumbing	7
Combined contributors to cracking	8
<u>Roofs</u>	8
Tiled roofs	8
Metal roofs	8
Colorbond roofing	9
Screws, nails and fasteners	9
Inspecting for leaks	9
Old roofs	9
Flat roofs	9
Gutters and downpipes	10
Maintenance & clearing	10
Downpipe size	10
Gutter shape and capacity	11
Exterior trim, barges, fascias	11
<u>Walls</u>	11
Exterior	11
Interior	12
Plasterboard	12
<u>Ceilings</u>	13
Plasterboard	13
Lath and plaster	13
Other ceiling types	13
Fibrous plaster	14
<u>Doors & Windows</u>	14
Window types	15
Awning	15
Casement	15
Double-hung	15
Sliding	15
<u>Sheds and storage</u>	15

Services	15
Electrical	15
Safety switches	16
Service lines	16
House wiring	16
Downlights fire risk	16
Other lamps fire risk.	17
Plumbing	17
Water plumbing	17
Waste plumbing	17
Current practice	17
Older installations	17
Salt damp and rising damp	18
SAFETY	19
Glazing	19
Mirrors	19
Safety glazing	19
Toughened glass	19
Laminated glass	19
Safety film	19
Wired glass	19
Blind cords	19
Fire safety	20
Escape	20
Smoke alarms	20
Fire extinguisher, fire blanket	20
Bushfire	20
Electrical	20
Hazardous Materials	21
Asbestos	21
Timber	21
Lead	21
Air quality	21
Off-gassing of new materials, paints etc	21
Carpets	22
Child safety	22
Hazardous substances:	22
Cleaning products	22
Solvents	22
Preventing access	22
Child fencing & access	22
Vehicle areas	22
Water safety	22
Stairs	22
Vehicles	23
Playing in cars	23

Playing with keys	23
Electrical safety	23
Shocks	23
Overloads	23
Fireplaces	24
Hot water scalding	24
First aid kit	24
Furniture	24
Falls	24
Dangerous structures	25
Deteriorated decks + balconies	25
Timber	25
Concrete	25
Outbuildings	26
Basketball rings and collapsing walls	26
Rats, possums and unwanted visitors	26
Ventilation & Sealing	26
Water vapour	26
Ceilings	27
Doors + windows	27
Stairs	27
Handrails and grabrails	27
Lighting	27
Security	28
Barriers to entry	28
Security screen doors	28
Glass reinforcement	28
Window grilles and shutters	28
Locks	28
Surveillance and detection	28
Peep holes	28
Remote surveillance cams	28
Alarms	29
TERMITES	30
Consequences of damage	30
I found some termites	30
How to reduce the risk of attack	31
In existing buildings	31
Cosy conditions	31
Surplus food	31
Posts	31
In new work	31
Detection and eradication	31
Observation	31

Ant caps and flashings	31
Baiting	31
Inside the house	31
Noisy termites	32
Links to more information	32
<u>ENERGY EFFICIENCY</u>	33
<u>Passive solar design</u>	33
Going solar	33
<u>Lighting</u>	34
<u>Home heating</u>	34
<u>Home cooling</u>	34
<u>Insulation</u>	35
<u>Hot water heating</u>	35
<u>Shading</u>	36
<u>FRAMING DIAGRAMS & JARGON</u>	37
<u>TYPICAL WALLS & FOOTINGS</u>	37
<u>TYPICAL WALLS & FOOTINGS</u>	38
<u>INDEX</u>	39

This appendix is a work in progress which has been created in response to requests for further information from clients who were unfamiliar with certain faults and maintenance issues. Because this document covers such a variety of age and type of home, some of the issues discussed may not be relevant now, but may become useful in the future. Friends or family members may have homes where these issues are relevant. Your suggestions for improving this document may be made to the author, David Bodycomb at artekton@bigpond.net.au.

Cracking in buildings

Key words:

Footing –


the part of a structure, generally at its bottom, which transfers the loads of the structure into the foundation

Foundation–

the soil, rock, sand or fill on which the building is supported

Overview

Much of Adelaide’s suburbs are built on reactive soils – soils that shrink and swell according to their moisture content. Ideally, if the moisture can be kept unchanged, the building won’t crack. In reality this is not possible. Irregular rainfall (see graph) and inadequate footings (usually in older homes) on reactive foundation soil will make cracking inevitable. The problem varies with locality and the type of construction, from nil to very



severe. Very severe cracking needs repair every 5-10 years, simply to maintain a tolerable level of comfort and cleanliness in the home, and if the problem is widespread in the building, the accumulating cost and disruption can soon make demolition and redevelopment far preferable. Fortunately, this is rare, but even in a relatively minor case, it is easy to be alarmed and fearful of purchase and persons unfamiliar with the condition, especially from outside Adelaide, can be initially perplexed about how the locals can tolerate it. They may reasonably believe that the building will soon fall down, but this is most unlikely and it is rare even for a single wall to need to be fully rebuilt.


On recently-developed sites, another cause of cracking may exist: subsidence of areas of un-compacted soil, which settle over time, leading to a loss of building support. In this case, underpinning may become necessary, which involves sometimes difficult excavation under or against the footing, followed by concreting of new support piers and/or beams.

Footings and foundations

Many older homes are constructed on footings that have little or no structural value except to occupy the distance between the wall (usually tons of brick or stone) and the ground, slightly below the surface. They have little or no ability to resist movements in the foundation, so all such movements end up being transferred into the building and

manifest as cracking. Over the years, repairs accumulate, movement continues, and we can end up with extremely rough and uneven wall surfaces inside and out.


Construction during recent decades has largely overcome problems of cracking by developments in soil science and engineering, giving us footings that resist or accommodate the effect of foundation movements. Generally, footings are designed to be strong enough to support part or all of the building without bending or breaking. Where this is not feasible, the footing may be articulated – that is, made in sections which are connected with a flexible joint, with the building above likewise jointed. Buildings whose footings are unable to resist the consequent foundation movements will always experience cracking unless the walls have




OLD-TYPE STONE FOOTING:
LITTLE RESISTANCE TO
FOUNDATION MOVEMENTS

CONCRETE FOOTING:
UNABLE TO RESIST FOUNDATION
MOVEMENTS WHICH EXCEED ITS
STIFFNESS

adequate flexibility (eg are fully framed) or if they are built of rigid units (eg bricks) then they must have adequate control joints. Control joints are simply strategically-placed gaps in the rigid parts of a building's structure – usually seen in brickwork as a vertical slot about 15mm wide or as a complete pause in the brickwork at each door and window, with any walling above or below the window being simply a panelled infill. Prior to about 1970, homes typically did not have control joints, so movement will show up as cracking. In this sense, a crack which opens and closes seasonally might be regarded as an ad hoc control joint. In this case it may be appropriate to repair the crack well then form a proper control joint, involving cutting through the wall then closing the gap with flexible sealant. This work should only be done be under the guidance of a builder, architect or engineer.



Modern footings are designed by an engineer using established knowledge of the particular soil type at the site. Samples are taken from the site, usually to a depth of several metres, using a drill or push-tube. This information, added to knowledge of steel and concrete structures, assists the engineer in designing a footing to support a particular building for a particular site, so as to resist or accommodate the likely movement of that site together with other loads imposed upon the structure. Despite the vast accumulation of knowledge on the subject of footing design, there are numerous opportunities for footing to fail, allowing the building to crack. These include excessive wetting or drying of the foundation beyond that anticipated by the engineer (common causes discussed below), mistakes in the footing design, or poor building work.





What can I do about it?

With changes in soil moisture being the most common cause of cracking in houses, the management of water, on the surface and below, deserves close attention as discussed below.

Drainage from hard surfaces

Drainage from hard surfaces (paving and concrete) should be directed to a location where it will not cause overwetting of the building foundation.

Poorly-graded surfaces can allow ponding to occur which can become slippery and hazardous.



Drainage to and from sloping sites

Most house sites in Adelaide are fairly flat and drainage is easily managed, with excess stormwater being directed out to the street water table (see sketch). Sites that are not sloping towards the street can present issues of potential damage caused by drainage onto, or from, neighbouring sites. Roof water can be sent uphill to the street, up to a metre or so, using sealed underground pipework. Because it will always contain some 'dead water' and